

PrintTex®

Softimage Lightbox

Fields of application

.02 .04 .05 .06 .07 .11

Specifications

	REF. 599180 173
	100 % polyester knit fabrics PVC-free
	ca. 155/ 252/ 310/ 505 cm ca. 61/ 99/ 122/ 199 inch other widths available on request
	B-s1, d0 DIN EN 13501-1 Class A ASTM E84-16
	ca. 205 g/m ² ca. 6.1 oz/yd ²
	ca. 0.36 mm ca. 360 µm
	rolls 50/ 100 m 55/ 109 yd
	blank: 5 DIN EN ISO 105-B02
	blank: 35.7 % DIN EN 410
	blank: 93.7 DIN 5033-1
	length: 2.2 % cross: 0.9 % DIN EN 14704-1
	indirect, direct light
	cold, ultrasonic cut

	length: 290.7 N cross: 1119.3 N DIN EN ISO 13934-1 - max. tensile strength
	length: 65.4 % cross: 34.0 % DIN EN ISO 13934-1 - max. tensile elongation
	length: 26.1 N cross: 13.7 N DIN EN ISO 13937-2 - trouser tear propagation

Printing methods

print	UV	Latex	Dyesub
Inside	•	•	
Outside			

Certifications



STANDARD
100
09 0.67573
Hohenstein RTT1

Certified for
HP Latex Inks





PrintTex® Softimage Lightbox

Fields of application

.02 .04 .05 .06 .07 .11



Ref.-Nr.: 599180 173 | Preview print sample



PONGS GROUP GMBH & CO. KG

Bahnhofstraße 21
07919 Pausa-Mühltröf
Germany

Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of $\pm 5\%$ is valid. Effective: 2024/03