

## ImagePerfect<sup>™</sup> 7806PA Haze (FR)

ImagePerfect™ Haze is a polymeric, transparent, matt calendered vinyl with a permanent, acrylic-based adhesive, with PerfectApply technology. It is used for decorative window installations, both cut graphics and also printed graphics.

ImagePerfect™ Haze is a transparent, matt, calendered Polymeric vinyl that is suitable for use on a wide variety of clean, dry surfaces. It will be primarily used as a decorative window film to create an etched (engraved) effect on windows or glass panels in architectural enhancement and advertising/display installations in locations such as retail environments and lifestyle business environments (bars, hotels, restaurants, casinos, theatres, etc). It will also be used for glass conspicuity for personal safety in locations with high footfall, such as shopping centres and educational establishments. The specially-formulated, flexible film has consistent matt levels and it can be cut easily and weeded quickly and the high-quality, PE-coated liner further promote excellent layflat, cutting and weeding characteristics. The permanent, advanced acrylic-based adhesive, has a low initial-tack and creates a strong final bond to ensure a secure and durable finish. For digital conversion, it is compatible with eco solvent, solvent, latex and UV-cured inks, to which end it will deliver high levels of print quality. Before production, to ensure suitability, we would recommend a print test. Haze PA is suited for dry application.

Attention: If printing, please make sure the printed media is completely dry before laminating. Before the media is applied, the surface should be completely cleaned. The use of IP Surface Cleaner and lint-free, IP Surface Cleaning Cloths is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Polymeric calendered vinyl
Colour	Transparent matt silver
Thickness	80mym
Weight	N/A
Adhesive	Advanced acrylic, permanent
Adhesive Strength	14N/25mm (Finat TM 1/24h)
Release Paper	PE-coated liner, 90g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	5 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2023 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom