# HP Latex 700 W Printer



## Win high-value jobs, equipped with white ink, and sharpen your sustainability edge with HP Latex



## Access white and produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.<sup>1</sup>
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinvl.

### Beat your deadlines with smart, efficient printing

- Fast saturated color up to 334 ft<sup>2</sup>/hr outdoor, 226 ft2/hr indoor.2
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 121 lb (55 kg).

### GO BEYOND—Lead with environmental certifications<sup>3</sup>

- Contribute to a comfortable<sup>4</sup> working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications<sup>3</sup>—including UL ECOLOGO®<sup>5</sup> and EPEAT.6
- Access the most sensitive spaces with odorless prints<sup>4</sup> and compatibility with a wide range of alternative substrates.
- Reduce your plastics consumption with cartonbased cartridge<sup>8</sup> and labelless supplies; free recycling via HP Planet Partners.<sup>9</sup>

## For more information, please visit http://www.hp.com/go/latex700series

## Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (1\*:4.16 – a:0,48-b:2,34) with 160% UF printmode using HP 832 1-liter White Latex Ink Cartridge. Visual opacity = 91%.

Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality

<sup>&</sup>lt;sup>3</sup> Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at https://hp.com/go/latex

Applicable to HP Latex Inks. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>5</sup> UL ECOLOGO® Certified HP 832, HP 872, HP 873, and 882 Latex Inks and HP 864, 865, 865, 886, 867, 869, and 870 PageWide XL Inks meet a range of stringent human health and environmental considerations. Verified as of the publishing date in September 2023. For more details, please refer to the UL ECOLOGO® database at https://spot.ul.com/main-app/products/catalog/ or see https://www.ul.com/EL 6 Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See https://epeat.net for registration status by country.

<sup>7</sup> HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See https://www.hp.com/go/mediasolutionslocator

<sup>8</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink

cartridges from 2018 to 2020.

<sup>9</sup> Program availability varies. For details, see https://hp.com/hprecycle

## **Technical specifications**

Print	
Printing modes	1130 ft²/hr - Max Speed (1-pass) 334 ft²/hr - High Speed (4-pass) 226 ft²/hr - Production Fast (6-pass) 183 ft²/hr - Production Quality, Textiles and Backlits (8-pass) 172 ft²/hr - High Saturation (12-pass) 128 ft²/hr - High Saturation Backlits and Textiles (14-pass) 183 ft²/hr - White Spot (60%) 99 ft²/hr - White Overflood (60%) 32 ft²/hr - White Underflood (100%) 22 ft²/hr - 3 Layers Day & Night (160%)¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	1L
Printheads	$10\ (2\ cyan/black, 2\ magenta/yellow, 2\ light\ cyan/light\ magenta, 2\ white, 1\ HP\ Latex\ Optimizer, 1\ HP\ Latex\ Overcoat)$
Long-term print-to-prin repeatability	nt95% of colors ≤ 1.5 dE2000 <sup>2</sup>
Media	
Handling	Roll feed, take-up reel, wiper roller $^3$ , media saver, automatic horizontal cutter (for vinyl, banner and canvas $^4$ , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles $^{\circ}$
Roll size	18 to 64-in rolls (23 to 64-in rolls with full support)
Maximum roll weight	121 lb
Maximum roll diameter	9.8 in
Thickness	Up to 19.7 mil
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D x	x H)
Printer	101.7 x 33.6 x 55.2 in
Shipping	110.2 x 44.5 x 50 in
Operating area	110 x 82.7 in
Weight	
Printer	589 lb
Shipping	823 lb
What's in the box	HP Latex 700 W Printer, printheads, maintenance cartridge, ink mix containers (x2), printer stand, take-up reel, media feed accessory, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental rang	jes
Operating temperature	59 to 86°F
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <4.7 W <sup>6</sup> (sleep) (<19 W <sup>7</sup> with DFE), <0.25 W (off)
	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13
Requirements	A max printer power cord; 9 A max curing power cord
Requirements  Certification	
Certification	A max printer power cord; 9 A max curing power cord  IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN
<b>Certification</b> Safety	A max printer power cord; 9 A max curing power cord  IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)  Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive)

## **Ordering information**

	Y0U23A	HP Latex 700 W Printer
	Accessories	
	21V10A 421S3A	HP Latex 600/700/800 User Maintenance Kit HP Latex Media Feed Accessory
	7HR16A 7HR18A	HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 Ink Collector Foams Kit
	7HR19A T7U73A	HP Latex 630/700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller
	supplies	

4UU93A	HP 836 White Latex Printhead
4UU94A	HP 836 Optimizer Latex Printhead
4UV29A	HP 832 1-liter White Latex Ink Cartridge
4UV75A	HP 832 1-liter Black Latex Ink Cartridge
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A	HP 836 Magenta/Yellow Latex Printhead
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead
4UV98A	HP 836 Overcoat Latex Printhead
4UU96A	HP 836 Latex Maintenance Cartridge
4UV83A	HP 832 Ink Mix Container

#### Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified<sup>8</sup>, FSC® certified<sup>9</sup>, meets AgBB criteria<sup>10</sup>)

HP Photo-realistic Poster Paper

HP Premium Satin Canvas

HP Prime Matte Air GP (REACH compliant<sup>11</sup>)
HP Premium Removable Gloss Adhesive Vinyl (REACH compliant<sup>11</sup>)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

#### Service and Support

U13DCE HP 2 year Next Business Day with Defective Media Retention

U13DHE HP 3 year Next Business Day with Defective Media Retention U13DMPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DSPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

<sup>1</sup> Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.

<sup>2</sup> The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012, 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.

a Wiper roller is an optional accessory.

Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.

Textile Kit Accessory required for long runs of textile and porous textile.

<sup>6</sup> Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.

version 3.1.

7 Total power measured in sleep mode including the Digital Front End contained on the product.

8 UL GREENGUARD Gold Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org

9 Trademark license code FSC-C115319.

10 With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-vellutation-of-huilding.

evaluation-of-building

11 This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.





















