

## Product Information

Transparent Application Tape made of an embossed cast Polypropylene film. PT 95 can be torn by hand in both directions. The product offers dimensional stability and excellent lay-flat properties.

Due to the high tack acrylic adhesive, computer cut letters, images and logos, made of cast or calendered CAD/CAM plotter films can easily be transferred.

Especially to be emphasised are the following properties:

- The excellent lay-flat property guarantees excellent lamination without wrinkles, even on large motifs.
- To guarantee an easy processing, the film can be torn by hand in both directions.
- Easy unwinding of the film with low static charge.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Suitable for dry and wet applications.

## Technical Data

<b>Carrier:</b>	Polypropylene film, pyramid surface	
<b>Adhesive:</b>	Acrylic, modified	
<b>Adhesion [N/cm]:</b>	1,70	+/- 10 %
<b>Thickness [mm]:</b>	0,14	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

## Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v).

When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard.

However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.