

KERNOWJET METALIK® - PERMANENT

With its permanent high-tack adhesive, KernowJet Metalik® Permanent is your perfect partner for lamination on a extensive range of smooth substrates or can be used for wallcoverings. It is ideal for 3-D labels/doming applications and a wide variety of permanent applications. The back of the film is silver regardless of the front-face colour.

WHY CHOOSE US?

KernowJet Metalik films are designed to fulfil all requirements of the Sign and Wide-Format Printing industry. KernowJet Metalik can be applied or laminated manually or mechanically, with wet or dry application techniques. Applied to perfectly smooth substrates like glass, the films have a mirror look finish. On demand, we can create specific metallized colours in different shades, for example metallic red, blue, and green. Imagination is your only limit.



FEATURES

- High-tack permanent adhesive
- Turns any smooth surface into metallic
- Perfect for laminating to boards
- Very smooth finish, close to a mirror effect
- Corrosion free – 3 years outdoor UV stability

UK, EU AND ROW PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
152µ KernowJet Metalik Silver Permanent 056SSI	1372mm 1524mm	45.7m	056SSI
152µ KernowJet Metalik Gold Permanent 056SGO	1372mm 1524mm	45.7m	056SGO

US PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
6.0mil KernowJet Metalik Silver Permanent 056SSI	54"	50' & 150'	056SSI
	60"*	150'	
6.0mil KernowJet Metalik Gold Permanent 056SGO	54"	50' & 150'	056SGO
	60"*	150'	

*Available for custom orders



KERNOW COATINGS

KERNOWJET®
LATEX, SOLVENT & UV

KERNOWJET METALIK®

PERMANENT



PRODUCTS ON A SILVER PLATTER

"This adhesive is the perfect solution for anyone looking to add a touch of luxury to their shop displays or sales areas."

Machine Compatibility:

Latex: ★★ ★

(Eco)Solvent: ★★ ★

UV: ★★ ★

Available Colours:

Gold

Silver

Rose Gold**

**Rose Gold available for custom orders.

KernowJet Metalik - Permanent

Certified for
HP Latex Inks



KEY FEATURES

- Anti-reflective bright white surface
- Scratch and water-resistant
- No need for lamination
- Stiff, perfect flatness

IDEALLY SUITED FOR

- Suitable for permanent lamination onto display boards & other smooth surfaces
- POS decoration with or without print
- Ideal for shop-fitting, perfumeries, luxury boutiques, and Christmas campaigns
- Turn any smooth surface into metallic
- Ideal for packaging with metallic effect, our silver film is recommended for Color Logic® software
- Combine permanent print and CAD applications, for example doming

	Typical Value	Units
Property	S054CGO/ S054CSI	
Construction		
Total Thickness	152 +/- 8 6.0 +/- 0.3	μ/mil
Total Weight	196 +/- 8	gsm
Face Material(without adhesive)		
Thickness	70 +/- 4 2.8 +/- 0.2	μ/mil
Weight	90 +/- 5	gsm
Adhesive		
Thickness	22+/-5 0.9+/-0.2	μ/mil
180° Peel Adhesion (SS)	21 - 23	N/25mm
Adhesive Application Temperature	+5 to +50 +41 to +142	°C °F
Adhesive Service Temperature	-40 to +180 -40 to +356	°C °F
PET Filmic Release Liner		
Liner Thickness	60 +/- 3 2.4 +/- 0.1	μ/mil
Liner Weight	83 +/- 2	gsm

Recommended conditions:

Printroom	10°C - 30°C (50°F - 86°F)	30% - 65% RH
Usage	-40°C - 180°C (-40°F - 356°F)	10% - 90% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 50% RH

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Regional certification differences apply.